



KR 535HK Tabber

*Lead edge, trail edge,
and side edge all in a
single pass!*

**Introducing the
KR 535HK Kirk Rudy's
newest Tabber.**

**Applies tabs to meet
the USPS specifications
for Self-mailers and
booklet tabbing
regulations.**



The KR 535 HK handles large 16" diameter rolls and runs all major types of tabs as well as pressure sensitive stamps and labels of various shapes and sizes. Multiple tabs or labels can be applied in a single pass. The KR 535HK runs in line with most standard addressing systems.

KR 535HK Tabber



****General Specifications:**

- **Electrical Requirements:** 220 VAC Single Phase 50 –60 Hz 15 amps
- **Maximum Operating Speeds:** Single tabbing: TBD
Double tabbing: TBD

Note: Speeds are dependent on material being fed.
- **Physical Size:** Length: 70"
Width: 26"
Height: 33 1/4" Tabletop 70" Overall
- **Products:** Tabs: Min 0.50" dia. Max 2.00" dia.
Tab Qty: 1 to 6 Tabs or Stamps
Labels: 3" W x 2"L standard - larger sizes optional
Materials: TBD

Features:

- Side register belts for tight tabs
- Quick setup
- Automatic tab location feature
- Side to side tabletop adjustment
- Industry standard motors and control
- Quick-release top belt control.
- Runs in-line with most addressing systems.

Options:

- Single crank hydro lift kit for height adjustment up to 6 inches.
KR 496F Friction feeder and KR415 Interface conveyor.

**Specifications subject to change without notification

**Guards have been removed for clarity; do not operate machine without guards in place